

Tandberg LTO2 Media



The Tandberg LTO2 Media is a highly reliable data cartridge with low error rates and improved magnetic tape physical properties. This cartridge has passed the million-head-pass test in a high-speed Ultrium 2 drive.

Tandberg Data's recording technologies enable the recording of servo track signals with greater accuracy and obtain excellent servo track signal characteristics through the increased data track density of the Ultrium 2 format.

Tape Characteristics	
Capacity	200 GB / 400GB*
Tape Type	Metal Particle
Overall Length	609 m
Tape Thickness	8.9 µm
Magnetic Properties	
Coercivity	2,100 (Oe)
Physical Specifications	
Dimensions	105.4 mm (W) x 102.0 mm (L) x 21.5 mm (H)
Weight	210 g
Tape Life	
Durability	1,000,000 passes
Estimated archive life	Up to 30 years (Signal decay of less than 5%)
Environmental	
Operating	
Ambient Temperature	10 to 45°C (50 to 113°F)
Non-Condensing Relative Humidity	10% to 80%
Maximum Wet Bulb Temperature	26°C (78°F)
Storage (Non-Archival)	
Temperature	16 to 32°C (60 to 90°F)
Non-Condensing Relative Humidity	20% to 80%
Maximum Wet Bulb Temperature	26°C (78°F)
Warranty	Limited lifetime warranty
Compatibility	Linear serpentine recording half-inch Ultrium 2 compliance tape drive

*Assuming 2:1 data compression rate

For more information, kindly contact your Tandberg Data sales representative or authorised distributor, or visit www.tandberg.com.sg

Tandberg Data ASA, Kjelsåsveien 161, P.	O. Box 134, Kjelsås, N-0411 Oslo, Norway			
Tel: +47 22 18 90 90	ndberg Data ASA, Kjelsåsveien 161, P.O. Box 134, Kjelsås, N-0411 Oslo, Norway Tel: +47 22 18 90 90 Fax: +47 22 18 95 50			

Tandberg Data (Asia) Pte Ltd, 20 Bendemeer Road, #04-05 Cyberhub, Singapore 339914 Tel: +65 6396 0786 Fax: +65 6396 0787

Tandberg Data (Asia) Pte Ltd Shanghai Rep Office, Suite 817, Pine City, 777 Zhao Jia Bang Road, Shanghai 200032 Tel: +86 21 6443 6126 Fax: +86 21 6443 6157

Your Dealer:		

